

GT-15^{MULTI}

LCD Monitor with Multitouch Screen



- High-end 38.1 cm (15") LCD monitor for most demanding applications
- Integrated multitouch screen with bezel-free glass surface
- Highly elegant design featuring an extremely robust construction
- Works without driver software (as of Windows 7)
- Complete package including USB cable, audio cable and PSU

Specifications

Display	LCD size / type	38.1 cm (15") TFT active matrix panel
	Touch technology	Projective capacitive
	Touch interface	USB
	Visible surface	304x228mm (HxV)
	Pixel pitch	0.297x0.297mm (HxV)
	Resolution	1024x768 pixel
	Display mode	VGA 720x400 (70 Hz), VGA 640x480 (60/66/72/75 Hz), SVGA 800x600 (56/60/72/75 Hz), XGA 1024x768 (60/70/75 Hz)
	Display colours	16.2 millions
	Contrast	500:1
	Brightness (capacitive)	225 cd/m ² (typical)
	Response time	8 ms (typical)
	Viewing angle	Horizontal: 140° / vertical: 125°
General	Video input format	Analogue RGB 0.7V peak to peak
	Video input frequency	Horizontal: 31.47 kHz~60.02 kHz / vertical: 56 Hz~75 Hz
	Video signal input	15-pin D-sub (female, analogue)
	Colour	Black
	Dimensions	322x364x206 mm (HxWxD)
	Weight / Shipping weight	5.54 kg / 7.7 kg
	Voltage	AC input 100~240V / DC 12V
	Power consumption	Operation: 25W / standby: 3W / off: 1W
	Mounting options	Stand / 75x75mm VESA wall mount
	Function keys	Power on/off, Select, Up, Down, Menu
	Audio	1W speakers, 2 channels
	Temperature - operation / storage	0°C~40°C / -20°C~60°C
Humidity - operation / storage	20%~80% / 10%~90% (non-condensing)	



Your Dealer