



this touchscreen is the perfect choice for placement on table-tops. A foldable foot supports the monitor in the back. It can be adjusted to different heights, so it is possible to use it upright, like a normal monitor or almost horizontal to operate and view it from above. The orientation of the pictures does not have to be rotated in this case. The light-intensive LCD display is easy to read even under difficult lighting conditions or from unfavourable angles.

The integrated touchscreen registers signals on its touch-sensitive surface and automatically transforms them into mouse signals. Simply connect the monitor to the USB port of the computer. Any software can be used with this touchscreen without the need of adjustments or driver installation.

To setup the monitor, it features an intelligent on-screen-display that allows adjustments from the front panel conveniently and menu-driven.

Specifications	
Display Features	
Screen	15 inch TFT LCD
Power Input	AC 90~264 V, 50~60 Hz.
Display Area	304x228 mm (HxV)
Contrast Ratio	300:1
Pixel Pitch	0.297x0.297 mm (HxV)
View Angle	R/L +60°~-60° U/D +55°~-65°
Resolution	XGA 1024x768 75 Hz (max.)
Operation Features	
Brightness	250 cd/m ²
Response Time	Tf/Tf=15/10ms
Interface	Analog RGB
Connectors	R/L Audio, 15-pin-D-SUB
User's Control	
Front Panel Controls	Auto Adjust, Menu, up, down, Select+/-, ESC, Volume
Physical Specification	
Dimensions	360x360x180 mm (HxWxD)
Net Weight	4.6 kg
Power	
Power Saving	VESA DPMS Standard
Power Consumption	30W (Typ.)
Resistive Touch Panel	
Input Mode	Stylus Pen or Finger
Operation Temp.	-10°C~70°C
Hardness	3H
Transparency	>80%
Controller Type	USB

